


# NAPOLI






**Up to 143 lm/W**  
**L80 B10 70.000h**

Instructions of use and Declaration of conformity:  
<https://elmromania.ro/produse/office/napoli-e2021-cri80/>

## Standard:



## Options:



	L	W	H
NAPOLI LED M600X600	596	596	57
NAPOLI LED M1200X300	1196	296	57
NAPOLI LED M1500X300	1496	296	57

# NAPOLI

TYPE	optic	CRI	CCT	Flux (lm)	Total Power (W)	Efficacy lm/W	UGR	TA	WEIGHT kg	unit / cart	unit /palet
NAPOLI LED M600X600 2 3880/830 DPB	DPB	80	3000	3880	31.5	123	<19	+10°C / +40°C	3.7	1	50
NAPOLI LED M600X600 2 4070/840 DPB	DPB	80	4000	4070	31.5	129	<19	+10°C / +40°C	3.7	1	50
NAPOLI LED M600X600 3 3010/830 DPB	DPB	80	3000	3010	23.0	131	<19	+10°C / +40°C	3.6	1	60
NAPOLI LED M600X600 3 3160/840 DPB	DPB	80	4000	3160	23.0	137	<19	+10°C / +40°C	3.6	1	60
NAPOLI LED M600X600 4 4200/830 DPB	DPB	80	3000	4200	31.7	132	<19	+10°C / +40°C	3.7	1	60
NAPOLI LED M600X600 4 4400/840 DPB	DPB	80	4000	4400	31.7	139	<19	+10°C / +40°C	3.7	1	60
NAPOLI LED M1200X300 2 4080/830 DPB	DPB	80	3000	4080	30.0	136	<19	+10°C / +40°C	3.7	1	50
NAPOLI LED M1200X300 2 4290/840 DPB	DPB	80	4000	4290	30.0	143	<19	+10°C / +40°C	3.7	1	50
NAPOLI LED M1500X300 2 6740/830 DPB	DPB	80	3000	6740	50.0	135	<19	+10°C / +40°C	4.5	1	50
NAPOLI LED M1500X300 2 7070/840 DPB	DPB	80	4000	7070	50.0	141	<19	+10°C / +40°C	4.5	1	50