

TEMPO CRI80


ELM ROMANIA
LED LIGHTING MANUFACTURED IN EUROPE




Up to 153 lm/W
L80 B10 123.000h

Instructions of use and Declaration of conformity:
<https://elmromania.ro/produse/office/tempo/>

Standard:



Options:



	L	W	H
TEMPO M6X6	596	596	33
TEMPO M12X3	1196	296	33
TEMPO M15X3	1496	296	33

TEMPO CRI80

ELM ROMANIA
LED LIGHTING MANUFACTURED IN EUROPE

TYPE	optic	CRI	CCT	Flux (lm)	Total Power (W)	Efficacy lm/W	UGR	TA	WEIGHT kg	unit / cart	unit /palet
TEMPO M6x6 3400/830	MP	80	3000	3400	27	126	<19	+10°C / +40°C	2.1	1	80
TEMPO M6x6 ML 1900-3400/830	MP	80	3000	1900-3400	13-27	146	<19	+10°C / +40°C	2.1	1	80
TEMPO M6x6 ML 3400-4100/830	MP	80	3000	3400-4100	27-33	126	<19	+10°C / +40°C	2.1	1	80
TEMPO M6x6 3600/840	MP	80	4000	3600	27	133	<19	+10°C / +40°C	2.1	1	80
TEMPO M6x6 ML 1900-3600/840	MP	80	4000	1900-3600	13-27	146	<19	+10°C / +40°C	2.1	1	80
TEMPO M6x6 ML 3600-4300/840	MP	80	4000	3600-4300	27-33	126	<19	+10°C / +40°C	2.1	1	80
TEMPO M6x6 3600/865	MP	80	6500	3600	27	133	<19	+10°C / +40°C	2.1	1	80
TEMPO M6x6 ML 1900-3600/865	MP	80	6500	1900-3600	13-27	146	<19	+10°C / +40°C	2.1	1	80
TEMPO M6x6 ML 3600-4300/865	MP	80	6500	3600-4300	27-33	133	<19	+10°C / +40°C	2.1	1	80
TEMPO M6x6 3600/830	OP	80	3000	3600	27	133	<22	+10°C / +40°C	2.0	1	80
TEMPO M6x6 ML 1900-3600/830	OP	80	3000	1900-3600	13-27	146	<22	+10°C / +40°C	2.0	1	80
TEMPO M6x6 ML 3600-4300/830	OP	80	3000	3600-4300	27-33	133	<22	+10°C / +40°C	2.0	1	80
TEMPO M6x6 3800/840	OP	80	4000	3800	27	141	<22	+10°C / +40°C	2.0	1	80
TEMPO M6x6 ML 2000-3800/840	OP	80	4000	2000-3800	13-27	153	<22	+10°C / +40°C	2.0	1	80
TEMPO M6x6 ML 3800-4550/840	OP	80	4000	3800-4550	27-33	141	<22	+10°C / +40°C	2.0	1	80
TEMPO M6x6 3800/865	OP	80	6500	3800	27	141	<22	+10°C / +40°C	2.0	1	80
TEMPO M6x6 ML 2000-3800/865	OP	80	6500	2000-3800	13-27	153	<22	+10°C / +40°C	2.0	1	80
TEMPO M6x6 ML 3800-4550/865	OP	80	6500	3800-4550	27-33	141	<22	+10°C / +40°C	2.0	1	80